




Double Wedge is available for 22 to 48 inch sizes, but .500 inches must be subtracted from the "B" dimension thus limiting your pipe O.D. range by .500 inches. The Double Wedge is only available on the "L" connectors.

Special sizes quoted upon request.

50 inch (or larger) Connectors have 2 Wedges or more.

Using Corrugated Pipe: Adapters are required when using Corrugated Pipe. Refer to the Corrugated Pipe Adapter Data Sheet for details.



Version 1.1\_2017

### SIZING CHART

P/N	Suggested Pipe O.D. Range (inches)	Hole Size Range (inches)		Connector Dimension (inches)		Pipe Clamps		Minimum Manhole Size Required (inches)
		A	B	C	D	Qty	P/N	
S206-18L	15.000 - 15.625	17.98 - 18.13	15.875	16	10.50	2	I-282	48/5
S206-20	15.625 - 17.000	19.98 - 20.13	17.875	17	10.50	2	I-282	48/5
S206-20L	17.000 - 17.625			18		2	I-306	
S206-22	17.625 - 19.000	21.98 - 22.13	19.875	19	10.50	2	I-318	48/5
S206-22L	19.000 - 19.625			20		2	I-348	
*S206-24A	18.000 - 19.500	23.98 - 24.13	21.875	18.75	10	4	I-180	48/5
S206-24	19.625 - 21.000	23.98 - 24.13	21.875	21	10.50	4	I-180	48/5
S206-24L	21.000 - 21.625			22		4		
S206-26	21.625 - 23.000	26.00 - 26.20	23.875	23	10.50	4	I-190	48/5
S206-26L	23.000 - 23.625			24		4	I-218	
S206-28	23.625 - 25.000	28.00 - 28.20	25.875	25	10.50	4	I-218	48/5
S206-28L	25.000 - 25.625			26		4		
S206-30	25.625 - 27.000	30.00 - 30.20	27.875	27	10.50	4	I-218	60/6
S206-30L	27.000 - 27.625			28		4	I-242	
S206-30L-32	27.000 - 27.625	32.00 - 32.20	27.875	28	10.50	4	I-242	60/6
S206-32	27.625 - 29.000	32.00 - 32.20	29.875	29	10.50	4	I-242	60/6
S206-32L	29.000 - 29.625			30		4		
S206-34	29.625 - 31.000	34.00 - 34.20	31.875	31	10.50	4	I-258	60/6
S206-34L	31.000 - 31.625			32		4		
S206-36	31.625 - 33.000	36.00 - 36.20	33.875	33	10.50	4	I-282	72/7
S206-36L	33.000 - 33.625			34		4		
S206-38	33.625 - 35.000	38.00 - 38.20	35.875	35	10.50	4	I-282	72/7
S206-38L	35.000 - 35.625			36		4	I-306	
S206-40	35.625 - 37.000	40.00 - 40.20	37.875	37	10.50	4	I-306	72/7
S206-40L	37.000 - 37.625			38		4		
S206-42	37.625 - 39.000	42.00 - 42.20	39.875	39	10.50	4	I-318	72/7
S206-42L	39.000 - 39.625			40		4	I-348	
S206-44	39.625 - 41.000	44.00 - 44.20	41.875	41	10.50	4	I-348	84/8
S206-44L	41.000 - 41.625			42		4		
S206-44L-46	41.000 - 41.625	46.00 - 46.20	41.875	42	10.50	4	I-348	84/8
S206-46	41.625 - 43.000	46.00 - 46.20	43.875	43	10.50	4	I-348	84/8
S206-46L	43.000 - 43.625			44		4	I-242	
S206-48	43.625 - 45.000	48.00 - 48.20	45.875	45	10.50	6	I-242	84/8
S206-48L	45.000 - 45.625			46		6	I-258	
S206-50	45.000 - 45.625	50.00 - 50.25	47.250	46	10.50	6	80667	96/9
S206-50L	45.625 - 47.000			47		6		
S206-52	47.000 - 47.625	52.00 - 52.25	49.250	48	10.50	6	80667	96/9
S206-52L	47.625 - 49.000			49		6		
S206-54	49.000 - 49.625	54.00 - 54.25	51.250	50	10.50	6	80667	96/9
S206-54L	49.625 - 51.000			51		6		

WWW.TRELLEBORG.COM/PIPE-SEALS