


Kor-N-Seal® I EX Series Connector (WP-EX Series)

Sizing Chart

Kor-N-Seal Connector P/N (inches)	Suggested Pipe O.D. Range (inches)	Hole Size Range (inches)	Connector Dimensions (inches)				Pipe Clamp P/N
			A	B	C	D	
S406-10AWP-EX	6.00 - 6.75	10.06 - 10.20	8.13	6.50	6	I-128	
S406-10WP-EX	7.50 - 8.00	10.06 - 10.20	8.13	8.50	6	I-180	
S406-10.5AWP-EX	6.00 - 6.75	10.53 - 10.70	8.63	6.50	6	I-128	
S406-10.5WP-EX	7.50 - 8.50	10.53 - 10.70	8.63	8.50	6	I-180	
S406-11BWP-EX	6.00 - 7.00	11.03 - 11.20	9.13	6.00	6	I-128	
S406-11AWP-EX	7.50 - 9.00	11.03 - 11.20	9.13	8.00	6	I-180	
S406-12CWP-EX	6.00 - 7.00	12.04 - 12.20	10.13	6.50	6	I-128	
S406-12BWP-EX	6.25 - 7.50	12.04 - 12.20	10.13	7.00	6	I-128	
S406-12AWP-EX	7.50 - 9.00	12.04 - 12.20	10.13	8.50	6	I-180	
S406-12WP-EX	9.00 - 10.00	12.04 - 12.20	10.13	10.00	6	I-180	
S106-12BWP-EX	5.75 - 7.00	12.04 - 12.20	10.13	6.50	8	I-128	
S106-12AWP-EX	7.00 - 8.50	12.04 - 12.20	10.13	8.00	8	I-180	
S106-12WP-EX	8.25 - 9.75	12.04 - 12.20	10.13	9.25	8	I-180	
S106-14AWP-EX	9.50 - 11.25	14.03 - 14.20	12.13	10.50	8	I-190	
S106-16BWP-EX	9.50 - 11.25	15.98 - 16.15	14.13	10.50	8	I-190	
S106-16AWP-EX	11.25 - 13.00	15.98 - 16.15	14.13	12.25	8	I-218	
S106-16WP-EX	13.00 - 14.00	15.98 - 16.15	14.13	14.00	8	I-242	
S106-20BWP-EX	14.00 - 15.50	19.95 - 20.10	18.25	15.00	8	I-306	
S106-20AWP-EX	15.50 - 17.00	19.95 - 20.10	18.25	16.50	8	I-306	
S106-20WP-EX	17.00-18.15	19.95 - 20.10	18.25	18.00	8	I-306	



*Refer to Installation Instructions for factory recommended torque values



WWW.TRELLEBORG.COM/PIPE-SEALS